

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

Claims 1-4: (CANCELED).

5. (CURRENTLY AMENDED) A pneumatic tire for passenger cars comprising a rubber-steel cord composite which comprises a steel cord, the steel cord having filaments which have different oscillations and are twisted at irregular pitches and having, in a planar image of the composite formed by X-rays passing through the composite, a fraction R of the total area occupied by the filaments of from 0.45 or more to 0.95 or less in an arbitrarily selected portion of the steel cord having a length of 15 mm in an axial direction of the cord,

wherein the length of 15 mm in an axial direction of the cord means a length of 15 mm in an axial direction of an actual cord and the fraction R of the total area occupied by the filaments is expressed as $R=F/A$, A representing the total area of the cord and F representing the area of the cord occupied by the filaments.

6. (ORIGINAL) A pneumatic tire for passenger cars according to Claim 5, wherein the filaments of the steel cord are present substantially independently of each other in a matrix rubber.

7. (ORIGINAL) A pneumatic tire for passenger cars according to Claim 5, wherein the steel cord has one of a $1 \times n$ structure and a $1+n$ structure, n being in a range of $2 \leq n \leq 7$.

8. (PREVIOUSLY PRESENTED) A pneumatic tire for passenger cars according to Claim 5, wherein the filaments constructing the steel cord have a diameter in a range of from 0.125 to 0.275 mm.

9. (PREVIOUSLY PRESENTED) A pneumatic tire for passenger cars according to Claim 5, further comprising a carcass, wherein the rubber-steel cord composite is used in the carcass of the pneumatic tire.

10. (CURRENTLY AMENDED) A pneumatic tire for passenger cars according to Claim 5, further comprising a side wall portion reinforced with a rubber reinforcing layer made of a rubber composition.

11. (PREVIOUSLY PRESENTED) A pneumatic tire for passenger cars according to Claim 9, wherein the carcass comprises: a turned-up ply reinforced with a cord of an organic fiber having a melting point of 245°C or higher, and

a down carcass ply comprising the rubber-steel cord composite in which a plurality of the steel cords disposed substantially parallel to each other is embedded in a matrix rubber, said down carcass ply being disposed between a side wall rubber and an outer face of the turned-up ply.

12. (WITHDRAWN) A pneumatic tire for passenger cars according to Claim 5, comprising

a carcass ply reinforced with polyester cords and/or polyamide cords; wherein the rubber-steel cord composite is disposed in a side wall portion, the composite in which a plurality of steel cords disposed substantially parallel to each other is embedded in a matrix rubber.

13. (PREVIOUSLY PRESENTED) A pneumatic tire for passenger cars according to Claim 9, wherein the carcass comprises a turned-up ply and a down ply, and the down ply comprises the rubber-steel cord composite in which a plurality of the steel cords disposed substantially parallel to each other is embedded in a matrix rubber, and is disposed between a side wall portion and an outer face of the turned-up ply, and any one of the turned-up ply and the down ply is a separate-type carcass ply which is separated into portions underneath a belt portion.

AMENDMENT UNDER 37 C.F.R. §1.116
Application Number 09/853,653

Our Ref: Q64382
Art Unit: 1733

14. (PREVIOUSLY PRESENTED) A pneumatic tire for passenger cars according to Claim 13, wherein any one of the turned-up ply and the down ply is separated into portions disposed under the belt portion with a distance of at least 20% of a width of the belt portion between the ply portions.